



One BIN only
for a CCT range



Lifetime



Certified



Certified



Certified



Warranty



Ra Available

IP Grade Available











Features

- 3014 side-emitting LEDs
- Epistar chips, LM-80 tested
- Ra90+, with high R9 & R13 value
- Good white color consistence between same or different batches
- Tube encased (IP67) & indoor (IP22) are available
- Cuttable every 3 LEDs for 12V, 6 LEDs for 24V
- 3M double sided tape for easy installation
- cULus Listed, 5 years warranty

Specifications

LED Type	SMD 3014	Dimmable	Yes
LED Q'ty/m	96pcs	IP grade	IP22 (IP67 available upon request)
Input Voltage	12V / 24VDC Constant Voltage	Installation	3M™ double sided tape (mounting clips for Ip67)
Power	7.68W	Working Temperature	-40~+80 °C
Cutting length	12V 31.25mm 3 LEDs 24V 62.5mm 6 LEDs	Max run	12V 2.5 meters 24V 5 meters
Strip Width	5mm / 8mm	Certification	E354137 cULus Listed, CE, RoHs
Viewing Angle	120°	Warranty	5 years ^①

Order Code	CCT/ Color	CRI	Lumen/M ^②
ALEDT3014-96UDL-30K	 2850-3025K	90+	520
ALEDT3014-96UDL-50K	 4830-5095K	90+	560
ALEDT3014-96UDL-65K	 6260-6680K	90+	560
ALEDT3014-96UDL-100K	 ≥11000K	90+	530
ALEDT3014-96UDL-R	 620-625nm	-	200
ALEDT3014-96UDL-G	 520-525nm	-	240
ALEDT3014-96UDL-B	 465-470nm	-	120
ALEDT3014-96UDL-Y	 594-596nm	-	480

Note 1: Contact AUSLED for exact warranty period and policy.

Dimension

